



Model: BFU* (UL) LED Filament Bulb



Technology

- Sapphire Based Filament
- Nitrogen filled for lower heat
- Glass Lens
- Water tight seal
- 35,000 hour life to L70



Style	A60/A19				C35			C35T		
Series	BFU01				BFU02			BFU02		
Power (Watt)	7	6	5 (Dimmable)	4	4 (Dimmable)	3	2	4 (Dimmable)	3	2
Size (mm)	60 X 105				35 X 100			35 X 125		
Glass Color	Clear/Frosted				Clear/Frosted			Clear/Frosted		
Base Type	E26/E27				E26/E27			E26/E27		
Voltage (vac)	100~120				100~120			100~120		
Beam Angle	360°				360°			360°		
*Color Temp	2300~2700K				2300~2700K			2300~2700K		
CRI	>80				>80			>80		
Lumen	820	620	510	430	450	320	200	320	230	120
Incandescent Equal(W)	75	60		40	40	25	10	40	25	10
Certification	UL/ES OR TUV				UL/ES OR TUV			UL/ES OR TUV		
Warranty	3 Years				3 Years			3 Years		
Dimmable	Optional				Optional			Optional		

*4000 and 5000K available

Part # Example: BFU01NXX407W27E26JC

Series	Model	Dim or Non-Dim	Watts	Volts (AC/DC)	Color	Base	Beam	Lens
BFU (UL)	01=A60	D = YES	XX2=2w	07=110/120	W27=2700K	E26	J=90	C=Clear (Std)
	02=C35 Candlebra	N = NO	XX3=3W XX4=4W		W40=4000K	E12		F=Frosted
			XX8=8W		W60=6000K	E14		CL=Clear Cone (BFU02) CF=Clear Flame (BFU02)
			XX8=8W					F=Frosted Cone (BFU02) FF=Frosted Flame (BFU02)

Incandescent Replacement Indoor/Outdoor

High-efficiency solid state sapphire based technology, with advanced nitrogen filled housing and glass optical diffuser, 70%+ savings in energy consumption, dimmable option, minimum 35,000 hour life, wide voltage and constant current design, shock & vibration resistant, mercury free, 100% recyclable, no ballast, no noise, no flickering, UL or TUV listed, Energy Star. Frosted Lens Optional