



LED Tube UL Rated 360° Light Output

Series: 92 Model: 13

Commercial / Industrial Superior Grade
T8 LED 280-320° Glass Tube UL,DLC,CE



Replaces T8, T10 and T12 Fluorescent
Available in 100~277 AC Version

**Power Input works with
original ballast or without
ballast (Direct AC)**

145Lm/W



- ✓ Glass Lens
- ✓ Frosted Milk
- ✓ CE, UL, RoHS
- ✓ "No" UV, IR, Ballast

Part#	Power	Volt (AC)	CCT	lm/W ±8%	CRI	Size (mm)	Replace Fluorescent Watts
9213NX1210W30APFO	12	100-277	3000	140	>80	1198 x 26	60
9213NX1210W40APFO	12	100-277	4000	140	>80	1198 x 26	60
9213NX1210W50APFO	12	100-277	5000	140	>80	1198 x 26	60

360° Light Output Glass LED Tube

360° LED Glass Tube with UL/DLC Certificate	
Model	9213
Length	1200mm/4ft
Wattage(w)	12W
Glass Type	Frosted
Driver	Internal
Wire Input	Opposing
Lamp Holder	G13
Dimmable	No
CRI(Ra>)	>83
Light output (lm)	1750Lm +-10%
Illumination 1M	400Lx
Illumination 2M	130Lx
Illumination 3M	70Lx
Light efficiency	145lm/w
Color Temp	3000,4000, 5000k
Power Supply	AC100-277V
Power Factor	≥.90
Tube View Angle	360°
Working Temp	-25~55°C
Long Life	50,000H
Qty/Ctn	25pcs
Carton Size(cm)	126*22*23
Gross Weight	8.72kg
Certificate	UL,DLC,CE,Rohs,Erp

Series	Model	Dim or not	Watt	Volts (AC)	Color	Base	Beam	Lens	Wired
92	13=4FT	N = NO	X12=12W	10=100~277	W27=3000K W40=4000K W50=5000K	A=G13	P=320	C=CLEAR F=FROSTED	O=Opposing