



Cordless Rechargeable Floodlight

Series: OF Model: 10
10W, 20W, 50W



- ✓PC Lens
- ✓50,000 hrs life
- ✓Clear Tempered Glass lens
- ✓CE, RoHS
- ✓"No" UV, IR, Ballast
- ✓Built in driver

Product Model	Power	Battery Li- Ion	Charging Time	Discharge Time	Size(mm)
OF10NX1002W60WGCY	10W	4800MAH	4H	5H	75*95*100
OF10NX2002W60WGCY	20W	8800MAH	4H	5H	180*115*140
OF10NX5002W60WGCY	50W	18000MAH	10H	5H	288*150*240

Portable Battery Powered Work Light Cool to the Touch – No Heat

Part # Key Example: OF10X2002W60WNCY

XX XX X XXX XX XXX X X X
↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑

Series	Model	Dimm or Non	Watts	Volts	Color	Cord	Beam °	Lens	Case
OF	10 = Cordless	N= Non-Dimm	X10=10W X20=20W X50=50W	02=12VDC 09=85~240VAC (Wall Mount)	W60=6000K	W=Wall Mount	N=150 Deg	C=Clear	Yellow

Electrical Parameters	
Power Supply	AC Wall mount/DC Auto
Input Voltage	AC : 85-265V
Lumen / W	100
Power Efficiency	≥90%
PF	≥0.92PF
Frequency	50/60Hz
Material	PC(Alu + PC)
IP Rating	IP65
Operating temperature	40°C ~ -20°C
Operating humidity	10% ~ 90%RH
Life	50000H
LED Type	Wafer Integration
Ra	> 70Ra
Efficiency	≥100 LM/W
Beam Angle	150°
Efficiency	≥90%